



## Product Data Sheet

**Product Name:** FutureCarbonX

**Description:** Super-concentrated hydrocarbon encapsulation chemical agent. FutureCarbonX chemically binds with hydrocarbons and other oil-based chemicals. This product greatly reduces LEL levels within 12 hours of application (60% reduction within 30 minutes usually). Excellent for use as a pre-treatment for tanks needing entry with high LEL. Moderate cleaning capabilities. Contains deodorant. Moderate foaming capabilities.

### Product Use & Applications

Tank Cleaning  
LEL Control  
Hydrocarbon Stripping  
Spill Control  
Odor Problems  
Fire Prevention

### Application Instructions

**Dilution Rate** 1:5 to 1:20 with water  
**Set Time** 30 minutes to 24 hours

**Special Instructions:**  
Use de-foaming agent for scrubbing applications

### Hazardous Information

Eye and skin irritant  
Flash Point Above 220°  
Biodegradable  
pH 10.5 to 11.5  
No unusual Hazards  
\* Do not let product freeze \*

### Packaging Information

5 gal bucket  
55 gal DOT drum  
275 gal tote w/protective enclosure

## Product Case History

Cleaning & Decommissioning of Numerous Gasoline UST's

Cleaning of 5 million gallon Petroleum tank

Petroleum Spill Clean up

[www.futureenvironmental.com](http://www.futureenvironmental.com)

(708) 479-6900